


FEATURES:

- ✓ Architectural luminaire with direct lighting distribution.
- ✓ Light source: COB LED.
- ✓ A high efficiency integral reflector combined with an opal lens insert provides excellent lighting distribution with a 40° beam.
- ✓ Circular internal louver is available in a wide range of finishes.
- ✓ Aluminum body of the luminaire comes with a built-in-driver, available in a black or white finish.
- ✓ Suitable for surface mounted and suspended installations.
- ✓ LED spot is rated for 60,000 hrs. L80 with +90 CRI.
- ✓ Has a proven record in office, commercial and retail installations.
- ✓ Custom modifications are available.
- ✓ ED luminaires are certified to CSA and UL standards.

reinventlight
SPECIFICATION:
ED TUBE+

SOURCE	RADIANCE	VOLTAGE	DRIVER	MOUNTING	REFLECTOR	FINISH	CCT
--------	----------	---------	--------	----------	-----------	--------	-----

Enter the Product Code into the boxes above.

SOURCE

- 15 W
- 20 W
- 25 W

RADIANCE

- DD - Direct

VOLTAGE

- UNV - 120/277V

DRIVER

- ST - On/Off
- DL - 0-10V Dim (1%)
- DA4 - DALI D4i
-

Specify dimming protocol.

MOUNTING

- SF - Surface Mount
- S6B - 6 ft Cord BK¹
- S6W - 6 ft Cord WH¹
- S ft²
- R2B - Stem 2 ft BK¹
- R2W - Stem 2 ft WH¹
- R ft²

 1. Canopy match the Cord color.
 2. Specify Suspension length and color.

REFLECTOR

- BK - Black
- WH - White
- SL - Silver

FINISH

- BK - Black¹
- WH - White²

 1. RAL 9005
 2. RAL 9003

CCT

- 30K - 3000 Kelvin/90CRI
- 35K - 3500 Kelvin/90CRI
- 40K - 4000 Kelvin/90CRI
-

Specify required CCT.

DIMENSIONS:

Width	Height
4.5 in	6.0 in

LUMEN OUTPUT:

Watts	30K	35K	40K
15 W	1400 lm	1430 lm	1460 lm
20 W	1910 lm	1950 lm	1990 lm
25 W	2350 lm	2400 lm	2450 lm

