



## FEATURES:

- ✓ Architectural luminaire with direct or direct/indirect distribution.
- ✓ Light source: LED boards.
- ✓ Diffused illumination is provided by a high efficiency frosted opal lens.
- ✓ Sleek body of the luminaire combines aluminum body with a high efficiency opal lens.
- ✓ Suitable for surface, suspended installations.
- ✓ Extruded aluminum body comes with a black or white finish.
- ✓ Also available with custom color options.
- ✓ LED Strips are rated for 60,000 hrs. L80 with +90 CRI.
- ✓ Has a proven record in office, commercial and retail installations.
- ✓ Custom modifications are available.
- ✓ ED luminaires are certified to CSA and UL standards.

reinventlight

## SPECIFICATION:

**ED DRUM+**  -  -  -  -  -  -  -  -  -  -

Enter the Product Code into the boxes above.

- ### SIZE

  - 2 ft
  - 3 ft
  - 4 ft
  -

Specify custom size.

### SOURCE

  - 25 W
  - 50 W
  - 75 W<sup>1</sup>

1. Available for 4ft & Custom sizes.  
2. Other Wattages are available.

### RADIANCE

  - DD - Direct
  - UD - Uneven

### VOLTAGE

  - UNV - 120/277V
  - 347V<sup>1</sup>

1. Verify availability.

### DRIVER

  - ST - On/Off
  - DL - 0-10V Dim (1%)
  - DLO - 0-10V Dim (to Off)
  - DL2 - 0-10V Dim (TW)
  - DLA - 0-10V Dim (Aux)
  - DA4 - DALI D4i
  - CV - Constant Voltage (RGBW)
  -

Specify dimming protocol.

- ### MOUNTING

  - C6B - 6 ft Canopy BK<sup>1</sup>
  - C6W - 6 ft Canopy WH<sup>1</sup>
  - C  ft<sup>2</sup>
  - S6B - 6 ft Cord BK<sup>1</sup>
  - S6W - 6 ft Cord WH<sup>1</sup>
  - S  ft<sup>2</sup>
  - R2B - Stem 2 ft BK<sup>3</sup>
  - R2W - Stem 2 ft WH<sup>3</sup>
  - R  ft<sup>2</sup>
  - SF - Surface Mount

1. Canopy will match the Cord color.  
2. Specify Suspension length and color.  
3. Stem Mounting, available only for 2ft size.

### LENS

  - OP - Opal

### FINISH

  - BK - Black<sup>1</sup>
  - WH - White<sup>2</sup>
  - CF/RAL

1. RAL 9005  
2. RAL 9003  
Specify required RAL number.

### CCT

  - 30K - 3000 Kelvin/90CRI
  - 35K - 3500 Kelvin/90CRI
  - 40K - 4000 Kelvin/90CRI
  - RGBW<sup>1</sup>
  - TW - Tunable White (27K-65K)<sup>2</sup>
  -

1. Available with DMX or CB.  
2. Available with DL2, DA4 or CB.  
Specify required CCT.

### OPTIONS

  - No Options<sup>1</sup>
  - DC - Dual Circuit<sup>2</sup>
  - EC - Emergency Circuit
  - CB - Casambi Bluetooth(TW, RGBW)
  - DMX - DMX (RGBW)
  - AWN - Athena Wireless Node (DLA)

1. Leave empty.  
2. Control Downlight/Uplight separately.

## LUMEN OUTPUT:



Watts	30K	35K	40K
25 W	2610 lm	2650 lm	2690 lm
50 W	5150 lm	5250 lm	5380 lm
75 W	7720 lm	7875 lm	8030 lm





Project:

Type:

**SIZE:**




**RADIANCE:**




Size	Diameter
2 ft	23.60 in
3 ft	35.40 in
4 ft	47.20 in


**MOUNTING:**




**SUSPENDED - STRAIGHT WIRE**  
 PF - Power Feed  
 NF - Non Power Feed



**SUSPENDED - CEILING CANOPY**  
 CC - Ceiling Canopy - Available for 2-3-4 ft sizes  
 PF - Power Feed  
 NF - Non Power Feed



**SUSPENDED - STEM**  
 Available only for 2ft size.  
 3/8" IPS Stem with Power Feed



**SURFACE MOUNT - (SF)**