



FEATURES:

- ✓ Architectural adjustable luminaire with direct lighting distribution.
- ✓ Light source: COB LED.
- ✓ High efficiency optical system is available with 20° narrow, 40° flood or 60° wide beam angles.
- ✓ An integrated TRIAC/ELV dimming driver is placed into a sleek minimalistic body of the luminaire.
- ✓ Available in a black or white finish.
- ✓ Comes standard with a Juno track adapter.
- ✓ LED spot is rated for 60,000 hrs. L80 with a +90 CRI.
- ✓ Has a proven record in office, commercial and retail installations.
- ✓ Custom modifications are available.
- ✓ ED luminaires are certified to CSA and UL standards.

reinventlight

SPECIFICATION:

ED TRS+ SOURCE - RADIANCE - VOLTAGE - DRIVER - MOUNTING - BEAM - FINISH - CCT

Enter the Product Code into the boxes above.

SOURCE

10 W

RADIANCE

DD - Direct

VOLTAGE

120V

DRIVER

ST - On/Off

DT - TRIAC

Specify required dimming method.

MOUNTING

JT-Juno Track

Specify track adapter.

BEAM

BN - Narrow 20°

BF - Flood 40°

BW - Wide 60°

FINISH

BK - Black¹

WH - White²

1. RAL 9005

2. RAL 9003

CCT

30K - 3000 Kelvin/90CRI


35K - 3500 Kelvin/90CRI

40K - 4000 Kelvin/90CRI

Specify required CCT.

DIMENSIONS:

Height	Length	Diameter
5.50 in	4.13 in	2.38 in



LUMEN OUTPUT:

Watts	30K	35K	40K
10 W	950 lm	1000 lm	1050 lm



Project:

Type: