



## FEATURES:

- ✓ Architectural adjustable luminaire with direct lighting distribution.
- ✓ Light source: COB LED.
- ✓ High efficiency optical system is available with 15° narrow, 35° medium or 50° flood beam angle.
- ✓ An integrated TRIAC/ELV dimming driver is placed into a sleek minimalistic body of the luminaire.
- ✓ Available in a black or white finish.
- ✓ Comes standard with a Juno track adapter.
- ✓ LED spot is rated for 60,000 hrs. L80 with a +90 CRI.
- ✓ Has a proven record in office, commercial and retail installations.
- ✓ Custom modifications are available.
- ✓ ED luminaires are certified to CSA and UL standards.

**reinventlight**

## SPECIFICATION:

**ED TRM+**  SOURCE -  RADIANCE -  VOLTAGE -  DRIVER -  MOUNTING -  BEAM -  FINISH -  CCT

Enter the Product Code into the boxes above.

### SOURCE

- 5 W
- 10 W
- 15 W

### MOUNTING

- JT-Juno Track
- Specify track adapter.

Specify track adapter.

### RADIANCE

- DD - Direct

### VOLTAGE

- 120V

### DRIVER

- ST - On/Off
- DT - TRIAC
- Specify required dimming method.

### BEAM

- BS - Spot 15°
- BM - Medium 35°
- BF - Flood 50°

### FINISH

- BK - Black<sup>1</sup>
- WH - White<sup>2</sup>

1. RAL 9005  
2. RAL 9003

### CCT


- 30K - 3000 Kelvin/90CRI
- 35K - 3500 Kelvin/90CRI
- 40K - 4000 Kelvin/90CRI
- Specify required CCT.

## DIMENSIONS:

Height	Length	Diameter
5.00 in	3.97 in	2.36 in

## LUMEN OUTPUT:

Watts	30K	35K	40K
5 W	530 lm	540 lm	550 lm
10 W	1075 lm	1100 lm	1125 lm
15 W	1520 lm	1550 lm	1580 lm



Project:

Type: