



FEATURES:

- ✓ Architectural luminaire with direct lighting distribution.
- ✓ Light source: COB LED.
- ✓ Built-in frosted lens controls the light and reduces the glare.
- ✓ Available with a standard or asymmetric semi-specular reflector.
- ✓ Round trim comes in a black and white finish.
- ✓ Suitable for recessed non-insulated ceilings or damp locations.
- ✓ LED Spot is rated for 60,000 hrs. L70 with +90 CRI.
- ✓ Has a proven record in office, commercial and retail installations.
- ✓ Custom modifications are available.
- ✓ ED luminaires are certified to CSA and UL standards.

reinventlight

SPECIFICATION:

ED LR+

SIZE	SOURCE	RADIANCE	VOLTAGE	DRIVER	HOUSING	BEAM	TRIM	CCT

Enter the Product Code into the boxes above.

SIZE

- ☐ 4 In
☐ 6 In

SOURCE

- ☐ 10 W
☐ 20 W
☐ 30 W*

* Not available for 4 In.

RADIANCE

- ☐ DD - Direct (100% Down)
 *Light Distribution.

VOLTAGE

- ☐ UNV - 120/277V
☐ 347V*
 *Not available for all configurations.

DRIVER

- ☐ ST - On/Off
☐ DL - 0-10V Dim (1%)
☐ *
 *Specify required dimming method.

HOUSING

- ☐ RT - Retrofit
☐ NC - New Const. Plate

BEAM

- ☐ BW - Wide 80°
☐ BA - Asymmetric*
 * Available for 4 In trim only.

TRIM

- ☐ BK - Black
☐ WH - White

CCT


- ☐ 30K - 3000 Kelvin/90CRI
☐ 35K - 3500 Kelvin/90CRI
☐ 40K - 4000 Kelvin/90CRI
☐ *
 *Specify required CCT.

DIMENSIONS:

Size	4 Inch	6 Inch
Width	6.250"	7.875"
Height	4.875"	5.875"
Cutout	5.000"	6.500"

LUMEN OUTPUT:

Watts	30K	35K	40K
10 W	1050 lm	1100 lm	1125 lm
20 W	1915 lm	1950 lm	1985 lm
30 W	2950 lm	3010 lm	3070 lm



Project:

Type: