



FEATURES:

- ✓ Architectural adjustable luminaire with direct lighting distribution.
- ✓ Light source: COB LED.
- ✓ High efficiency optical system is available with 20° Spot, 40° Flood or 60° wide Flood Beam angle.
- ✓ Integrated TRIAC/ELV dimming driver is placed into sleek minimalistic body of the luminaire.
- ✓ Available in black or white finish.
- ✓ Comes standard with Juno track adapter.
- ✓ LED spot is rated for 60,000hrs. L70 with +90 CRI.
- ✓ Has a proven record in office, commercial and retail installations.
- ✓ Custom modifications are available.
- ✓ ED luminaires are certified to CSA and UL Standards.

reinventlight

SPECIFICATION:

SOURCE

-
- 10WLED

RADIANCE

-
- DD - Direct (100%Down)
-
- *Light Distribution.

VOLTAGE

-
- 120V
-
-
- 277V

DRIVER

-
- ST - Standard (Non-Dimming)
-
-
- DT - TRIAC

MOUNTING

-
- JT-Juno Track
-
-
-
- *
-
- *Other track adapters are available.

REFLECTOR

-
- SP - Spot
-
-
- FL - Flood
-
-
- WF - Wide Flood

FINISH


-
- BK - Black
-
-
- WH - White

CCT

-
- 30K - 3000Kelvin/90CRI
-
-
- 35K - 3500Kelvin/90CRI
-
-
- 40K - 4000Kelvin/90CRI
-
- *Other options are available.

DIMENSIONS:

Height	Width	Diameter
5.500"	4.125"	2.375"


LUMEN OUTPUT:

Watts	30K	35K	40K
10W	950 lm	1000 lm	1050 lm



Project: _____

Type: _____