



## FEATURES:

- ✓ Architectural adjustable luminaire with direct lighting distribution.
- ✓ Light source: COB LED.
- ✓ High efficiency optical system is available with 20° Narrow, 40° Flood or 60° Wide Beam Angle.
- ✓ An integrated TRIAC/ELV dimming driver is placed into a sleek minimalistic body of the luminaire.
- ✓ Available in a black or white finish.
- ✓ Comes standard with Juno track adapter.
- ✓ LED spot is rated for 60,000 hrs. L70 with a +90 CRI.
- ✓ Has a proven record in office, commercial and retail installations.
- ✓ Custom modifications are available.
- ✓ ED luminaires are certified to CSA and UL standards.

reinventlight

## SPECIFICATION:

**ED TRS+**

SOURCE	RADIANCE	VOLTAGE	DRIVER	MOUNTING	BEAM	FINISH	CCT

Enter the Product Code into the boxes above.

### SOURCE

- ☐ 10 W

### RADIANCE

- ☐ DD - Direct (100% Down)  
\*Light Distribution.

### VOLTAGE

- ☐ 120V

### DRIVER

- ☐ ST - On/Off  
☐ DT - TRIAC  
☐  \*  
 \*Specify required dimming method.

### MOUNTING

- ☐ JT-Juno Track  
☐  \*  
 \*Other track adapters are available.

### BEAM

- ☐ BN - Narrow 20°  
☐ BF - Flood 40°  
☐ BW - Wide 60°

### FINISH

- ☐ BK - Black  
☐ WH - White

### CCT


- ☐ 30K - 3000 Kelvin/90CRI  
☐ 35K - 3500 Kelvin/90CRI  
☐ 40K - 4000 Kelvin/90CRI  
☐  \*  
 \*Specify required CCT.

## DIMENSIONS:

Height	Width	Diameter
5.500"	4.125"	2.375"

## LUMEN OUTPUT:

Watts	30K	35K	40K
10 W	950 lm	1000 lm	1050 lm



Project:

Type: