

FEATURES:

- ✓ Architectural luminaire with direct lighting distribution.
- ✓ Light source: 11" LED Modular Board.
- ✓ Dark Optic provides superior lighting distribution with precise low glare illumination.
- ✓ 7 cell LEDiL reflector is available in several standard finishes.
- ✓ Offered with regular 50°/16UGR and flood 80°/19UGR internal optic.
- ✓ Low profile steel body housing contains a built-in driver.
- ✓ Suitable for non-insulated recessed installations into T-Bar or drywall.
- ✓ Has a proven record in office, commercial and retail installations.
- ✓ LED's are rated for 60,000hrs. L80 with +90 CRI.
- ✓ Custom modifications are available.
- ✓ ED luminaires are certified to CSA and UL Standards.

reinventlight

SPECIFICATION:

ED LINE2+ — — — — — — — — — —

Enter the Product Code into the boxes above.

SOURCE

- 20W LED
- 30W LED

RADIANCE

- DD - Direct (100%Down) *Light Distribution.

VOLTAGE

- 120V
 - 277V
 - 347V*
- * Not available for all configurations.

DRIVER

- ST - Standard (Non-Dimming)
- DL - 0-10V Dimming (1%)
- DA - DALI
- BT - Bluetooth
- EM - Emergency*
- **

*Emergency battery pack.
** Please specify dimming method.

MOUNTING

- RS - Recessed
- DW - Drywall

REFLECTOR

- BK - Black
- WH - White
- SL - Silver

LENS

- RB - Regular 50°
- FB - Flood 80°

FINISH

- BK - Black
- WH - White

CCT

- 30K/90CRI - 3000Kelvin
- 35K/90CRI - 3500Kelvin
- 40K/90CRI - 4000Kelvin

*Other options are available.

OPTIONS


- No Options*
 - DOS - Daylight & Occupancy Sensor
- *Leave Empty.

DIMENSIONS:

Length	Width	Height
23.75"	23.75"	1.50"

LUMEN OUTPUT:

Watts	30K	35K	40K
20W	2450lm	2500lm	2550lm
30W	3675lm	3750lm	3825lm



Project:

Type: