

FEATURES:

- ✓ Architectural luminaire with direct lighting distribution.
- ✓ Light source: LED board (5.5"/11"/22"/24").
- ✓ Diffused illumination is provided by high efficiency opal inserted or optional low glare microprismatic lens.
- ✓ Suitable for suspended and row mounted installations.
- ✓ Fixture body with integrated driver is made from light weight steel.
- ✓ Available with matt black or white finish.
- ✓ LED Strips are rated for 60,000hrs. L80 with +90 CRI.
- ✓ Has a proven record in office, commercial applications.
- ✓ Custom modifications are available.
- ✓ ED luminaires are certified to CSA and UL Standards.

reinventlight

SPECIFICATION:

ED EDGE+ — — — — — — — — —

Enter the Product Code into the boxes above.

SOURCE

- ☐ 35 W
☐ 45 W

RADIANCE

- ☐ DD - Direct

VOLTAGE

- ☐ UNV - 120/277V
☐ 347V¹
 1. Verify availability.

DRIVER

- ☐ ST - On/Off
☐ DL - 0-10V Dim (1%)
☐ DA4 - DALI D4i
☐
 Specify dimming protocol.

MOUNTING

- ☐ S4-Suspension 4 ft
☐ S6-Suspension 6 ft
☐ S ft
☐ SF - Surface Mount
 *Please specify required Length.

LENS

- ☐ OP - Opal
☐ PR - Prismatic

FINISH

- ☐ BK - Black¹
☐ WH - White²
 1. RAL 9005
 2. RAL 9016

CCT

- ☐ 30K - 3000 Kelvin/90CRI
☐ 35K - 3500 Kelvin/90CRI
☐ 40K - 4000 Kelvin/90CRI
☐ RGBW¹
☐ TW - Tunable White (27K-65K)²
☐
 1. Available with DMX or CB.
 2. Available with DL2, DA4 or CB.
 Specify required CCT.

OPTIONS

- ☐ No Options¹
☐ DOS - Daylight & Occupancy Sensor (DLA)
 1. Leave empty.

DIMENSIONS:

Length	Width	Depth
47.25 in	7.125 in	2.250 in

LUMEN OUTPUT:

Watts	30K	35K	40K
35 W	3420 lm	3500 lm	3580 lm
45 W	4400 lm	4500 lm	4600 lm



Project:

Type: