



## FEATURES:

- ✓ Architectural adjustable luminaire with direct lighting distribution.
- ✓ Light source: COB LED.
- ✓ High efficiency optical system is available with 20° narrow, 40° flood or 60° wide beam angles.
- ✓ An integrated TRIAC/ELV dimming driver is placed into a sleek minimalistic body of the luminaire.
- ✓ Available in a black or white finish.
- ✓ Comes standard with a Juno track adapter.
- ✓ LED spot is rated for 60,000 hrs. L80 with a +90 CRI.
- ✓ Has a proven record in office, commercial and retail installations.
- ✓ Custom modifications are available.
- ✓ ED luminaires are certified to CSA and UL standards.

reinventlight

## SPECIFICATION:

**ED TRS+**  SOURCE -  RADIANCE -  VOLTAGE -  DRIVER -  MOUNTING -  BEAM -  FINISH -  CCT

Enter the Product Code into the boxes above.

### SOURCE

10 W

### RADIANCE

DD - Direct

### VOLTAGE

120V

### DRIVER

ST - On/Off

DT - TRIAC

Specify required dimming method.

### MOUNTING

JT-Juno Track

Specify track adapter.

### BEAM

BN - Narrow 20°

BF - Flood 40°

BW - Wide 60°

### FINISH

BK - Black<sup>1</sup>

WH - White<sup>2</sup>

1. RAL 9005

2. RAL 9003

### CCT

30K - 3000 Kelvin/90CRI


35K - 3500 Kelvin/90CRI

40K - 4000 Kelvin/90CRI

Specify required CCT.

## DIMENSIONS:

Height	Length	Diameter
5.50 in	4.13 in	2.38 in



## LUMEN OUTPUT:

Watts	30K	35K	40K
10 W	950 lm	1000 lm	1050 lm



Project:

Type: