
FEATURES:

- ✓ Architectural luminaire with direct lighting distribution.
- ✓ Light source: 11" Curved LED board.
- ✓ Dark Optic provides superior lighting distribution with precise low-glare illumination.
- ✓ 7 cell LEDiL curved reflector is available in several standard finishes.
- ✓ Offered with Flood 50°/16UGR and Wide 80°/19UGR internal optics.
- ✓ Low profile steel body housing contains a built-in driver.
- ✓ Suitable for non-insulated recessed installations into T-Bar or drywall.
- ✓ Has a proven record in office, commercial and retail installations.
- ✓ LED's are rated for 60,000 hrs. L80 with +90 CRI.
- ✓ Custom modifications are available.
- ✓ ED luminaires are certified to CSA and UL standards.

reinventlight
SPECIFICATION:


Enter the Product Code into the boxes above.

SOURCE

20 W
 30 W

RADIANCE

DD - Direct

VOLTAGE

UNV - 120/277V
 347V¹

1. Verify availability.

DRIVER

ST - On/Off
 DL - 0-10V Dim (1%)
 DLO - 0-10V Dim (to Off)
 DLA - 0-10V Dim (Aux)
 DA4 - DALI D4i

Specify dimming protocol.

MOUNTING

RS - Recessed

BEAM

BF - Flood 50°
 BW - Wide 80°



BLACK

REFLECTOR

SB - Black
 SW - White



WHITE

FINISH

BK - Black¹
 WH - White²

 1. RAL 9005
 2. RAL 9003

CCT

30K - 3000 Kelvin/90CRI
 35K - 3500 Kelvin/90CRI
 40K - 4000 Kelvin/90CRI

Specify required CCT.


OPTIONS

No - Options¹
 EM - Emergency Battery²
 JD - JDRF Autonomy Sensor (DA4)
 DOS - Daylight & Occupancy Sensor (DLA)
 AWN - Athena Wireless Node (DLA)

 1. Leave empty.
 2. Emergency battery pack.
 Specify required option.

DIMENSIONS:

Length	Width	Height	Radius
23.75"	23.75"	1.50"	7.00"


LUMEN OUTPUT lm/W

Watts	30K	35K	40K
20 W	2450 lm	2500 lm	2550 lm
30 W	3675 lm	3750 lm	3825 lm


Project:
Type: