



FEATURES:

- ✓ Architectural adjustable luminaire with direct lighting distribution.
- ✓ Light source: COB LED.
- ✓ High efficiency optical system is available with 15° narrow, 35° medium or 50° flood beam angle.
- ✓ An integrated TRIAC/ELV dimming driver is placed into a sleek minimalistic body of the luminaire.
- ✓ Available in a black or white finish.
- ✓ Comes standard with a Juno track adapter.
- ✓ LED spot is rated for 60,000 hrs. L80 with a +90 CRI.
- ✓ Has a proven record in office, commercial and retail installations.
- ✓ Custom modifications are available.
- ✓ ED luminaires are certified to CSA and UL standards.

reinventlight

SPECIFICATION:

ED TRM+ SOURCE — RADIANCE — VOLTAGE — DRIVER — MOUNTING — BEAM — FINISH — CCT

Enter the Product Code into the boxes above.

SOURCE

- 5 W
- 10 W
- 15 W

RADIANCE

- DD - Direct

VOLTAGE

- 120V

DRIVER

- ST - On/Off
 - DT - TRIAC
 -
- Specify required dimming method.

MOUNTING

- JT-Juno Track
 -
- Specify track adapter.

BEAM

- BN - Narrow 15°
- BM - Medium 35°
- BF - Flood 50°

FINISH

- BK - Black¹
 - WH - White²
1. RAL 9005
2. RAL 9003

CCT


- 30K - 3000 Kelvin/90CRI
 - 35K - 3500 Kelvin/90CRI
 - 40K - 4000 Kelvin/90CRI
 -
- Specify required CCT.

DIMENSIONS:

Height	Length	Diameter
5.00 in	3.97 in	2.36 in

LUMEN OUTPUT:

Watts	30K	35K	40K
5 W	530 lm	540 lm	550 lm
10 W	1075 lm	1100 lm	1125 lm
15 W	1520 lm	1550 lm	1580 lm



Project:

Type: