

## FEATURES:

- ✓ Architectural luminaire with direct lighting distribution.
- ✓ Light source: 11" Curved LED board.
- ✓ Dark Optic provides superior lighting distribution with precise low-glare illumination.
- ✓ 7 cell LEDiL curved reflector is available in several standard finishes.
- ✓ Offered with Flood 50°/16UGR and Wide 80°/19UGR internal optics.
- ✓ Low profile steel body housing contains a built-in driver.
- ✓ Suitable for non-insulated recessed installations into T-Bar or drywall.
- ✓ Has a proven record in office, commercial and retail installations.
- ✓ LED's are rated for 60,000 hrs. L80 with +90 CRI.
- ✓ Custom modifications are available.
- ✓ ED luminaires are certified to CSA and UL standards.

**reinventlight**

## SPECIFICATION:

**ED LINE 0+**  —  —  —  —  —  —  —  —  —  —

Enter the Product Code into the boxes above.

### SOURCE

- ☐ 20 W  
☐ 30 W  
☐ 40 W

### RADIANCE

- ☐ DD - Direct

### VOLTAGE

- ☐ UNV - 120/277V  
☐ 347V<sup>1</sup>  
 1. Verify availability.

### DRIVER

- ☐ ST - On/Off  
☐ DL - 0-10V Dim (1%)  
☐ DLO - 0-10V Dim (to Off)  
☐ DA4 - DALI D4i  
☐ EM - Emergency Driver<sup>1</sup>  
☐   
 1. Emergency battery pack. Specify dimming protocol.

### MOUNTING

- ☐ RS - Recessed  
☐ DW - Drywall

### BEAM

- ☐ BF - Flood 50°  
☐ BW - Wide 80°

### REFLECTOR

- ☐ SB - Black  
☐ SW - White  
☐ SL - Silver

### FINISH

- ☐ BK - Black<sup>1</sup>  
☐ WH - White<sup>2</sup>  
 1. RAL 9005  
 2. RAL 9003

### CCT

- ☐ 30K - 3000 Kelvin/90CRI  
☐ 35K - 3500 Kelvin/90CRI  
☐ 40K - 4000 Kelvin/90CRI  
☐   
 Specify required CCT.

### OPTIONS

- ☐ No Options<sup>1</sup>  
☐ CB - Casambi/Bluetooth  
☐   
 1 Leave empty. Specify required option.




## DIMENSIONS:

Length	Width	Height	Radius
23.75 in	23.75 in	1.50 in	7.00 in

## LUMEN OUTPUT:

Watts	30K	35K	40K
20 W	1320 lm	1350 lm	1380 lm
30 W	2635 lm	2700 lm	2765 lm
40 W	3950 lm	4050 lm	4150 lm



Project:

Type: